



FRIDA

78

Exposed downlights



BK *

FRIDA 7W 3000K / 4000K

LED integrated

voltage: 230V

IP54

technical specification



LED 7W 500lm 3000K

LED 7W 550lm 4000K

installation place inlet opening 7-8cm

beam angle: 24°

LED

COLOUR / NEW INDEX NO.

- 3000K WHITE (WH) **AZ4525**
- 3000K BLACK (BK) **AZ4523**
- 4000K WHITE (WH) **AZ4526**
- 4000K BLACK (BK) **AZ4524**



Ø 8,5

TILT 90°

ROTATION 350°



WH *

FRIDA 12W 3000K / 4000K

LED integrated

voltage: 230V

IP54

technical specification



LED 12W 1100lm 3000K

LED 12W 1100lm 4000K

installation place inlet opening 7-8cm

beam angle: 24°

LED

COLOUR / NEW INDEX NO.

- 3000K WHITE (WH) **AZ4529**
- 3000K BLACK (BK) **AZ4527**
- 4000K WHITE (WH) **AZ4530**
- 4000K BLACK (BK) **AZ4528**



Ø 10

TILT 90°

ROTATION 350°



BK

BK

WH

WH

* - EXPLANATION SHORTCUT PAGE 2 (E)

FRIDA

Exposed downlights

79

