


# Linus new

BOUNCE LIGHT INCLUDED (•)

|                   |         |
|-------------------|---------|
| Source            | LED SMD |
| Driver included   | 1-10V   |
| Drivers available | No      |
| CCT               | 3000 K  |
| CRI               | ≥80     |

|                  |          |
|------------------|----------|
| LED life         | 50.000 h |
| Insulation class | I        |
| IP               | 20       |
| Material         | Aluminum |
| Warranty         | 5 years  |

### WALL - LED SMD Driver 1-10V included




1,250 Kg / 0,0112 m³

| Power  | Beam   | Flux      | CCT    | Finish | Code   | €                      |
|--------|--------|-----------|--------|--------|--------|------------------------|
| 34 W   | 104°   | 1950 Lm   | 3000 K | White  | 233840 | 150 <small>new</small> |
| 34 W • | 104° • | 1900 Lm • |        | Black  | 242019 | 150 <small>new</small> |

### STRUCTURE CONNECTOR Not included/Optional



| Code   | €                    |
|--------|----------------------|
| 233666 | 5 <small>new</small> |



2,550 Kg / 0,0112 m³


### PENDANT - LED SMD Driver 1-10V included

| Power  | Beam   | Flux      | CCT    | Finish | Code   | €                      |
|--------|--------|-----------|--------|--------|--------|------------------------|
| 34 W   | 104°   | 1950 Lm   | 3000 K | White  | 241968 | 165 <small>new</small> |
| 34 W • | 104° • | 1900 Lm • |        | Black  | 241975 | 165 <small>new</small> |

### STRUCTURE CONNECTOR Not included/Optional




| Code   | €                    |
|--------|----------------------|
| 241982 | 5 <small>new</small> |



0,260 Kg / 0,0003 m³

### CORNER Not included/Optional

| Power | Beam | Flux   | CCT    | Finish | Code   | €                     |
|-------|------|--------|--------|--------|--------|-----------------------|
| 3 W   | 104° | 270 Lm | 3000 K | White  | 241999 | 35 <small>new</small> |
|       |      |        |        | Black  | 242002 | 35 <small>new</small> |



| m | lx  | øm    |
|---|-----|-------|
| 1 | 572 | 2,56  |
| 2 | 143 | 5,12  |
| 3 | 64  | 7,68  |
| 4 | 36  | 10,24 |
| 5 | 23  | 12,80 |

CRI≥80 34W 104°+104° 1950+1900 Lm 3000 K