## ideal lux. | Quick

IΡ

Material

Warranty

Net Weight

Volume

20

Aluminum

5 years

0,760 Kg

0,0038 m<sup>3</sup>





Extruded aluminum cylindrical tracklight suitable for installation on three-phase track. White or black powder coating, 355° turning head and 90° adjustable, the power driver is included and located in the cylindrical body of the projector itself. Dimmable 1-10 or DALI version available, Light source with integrated

355° turning head and 90° adjustable, the power driver is included and located in the cylindrical body of the projector itself. Dimmable 1-10 or DALI version available. Light source with integrated COB LED technology for maximum efficiency, available with a color temperature of 3000K or 4000K; Energy efficient LED with high color rendering, up to CRI  $\geq$  90; starting binning  $\leq$ 3-Step MacAdam; symmetrical beam optic with three different emission angles and glare control (UGR <19); assembly and disassembly without tools; IP20 protection; insulation class I. Ideal for installation in big rooms, where great flexibility and color rendering is required, such as MUSEUM, COMMERCIAL and RETAIL spaces.

Pobrano z mamadecor.pl

TRACKLIGHTS









## Pobrano z mamadecor.pl NOT INCLUDED | OPTIONAL

## ideal lux. | Quick



Code Item name 222608 QUICK 15W / 21W HONEYCOMB

Code Item name Code Item name 222592 QUICK 15W / 21W LENS 15° 253558 QUICK 15W / 21W LENS 45°

Code Item name



