ideal lux.





Pobrano z mamadecor.pl rev. 24-08-2022

General info

Technical - Spotlights and Tracks

Indoor track mounted adjustable projector with integrated LED sources and direct light emission

Ean	8021696285368
Item	FOX 08W CRI90 41° 3000K ON-OFF WH
Installation	Eutrac 3-phase track (Ceiling, Wall)
Guarantee	5 years
Gross weight	0.35 kg
Volume	0.001518 m³

Technical info

Net weight	0.3 kg	
Insulation class	I	
Protection index	IP20	
Operating temperature	0° ~ +40 °C	
Dimmer	Non-dimmable, On-Off	
Power output	220-240 V AC 50/60 Hz	
Power supply	In-built, included	
	YES (by qualified operators only), electronic	
Adjustability	vert. 0°-90° , orizz. 0°-355°	
Accessories not included	Single connection on-off, Link on-off profile	

70 100 100 100 100 52

Source info

Integrated source	Integrated LED module
Repleaceable source	YES (by qualified operators only)
Power	8W
Emission	Direct
Max consuption	max 8,00 W
Features LED	LED COB BRIDGELUX
сст	3000 K
Duration LED (t. 25°c)	30000 h
CRI	> 90
SDCM	3
Light beam	41°
Light beam flux	750 lm
Useful light flux	700 lm
Standby power	< 0.50