Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's | name or | trade mark: | LUTEC |
|------------|---------|-------------|-------|
|------------|---------|-------------|-------|

Supplier's address: LUTEC EUROPE NV, Herentalsebaan 425, 2160 Wommelgem Wommelgem, BE

| Model identifier: | 5104001118M |
|-------------------|-------------|
|-------------------|-------------|

| Type of light source | Type | of lig | ht so | ource: |
|----------------------|------|--------|-------|--------|
|----------------------|------|--------|-------|--------|

| Lighting technology used: | LED | Non-directional or directional: | NDLS |
|-------------------------------|---------|---------------------------------|------|
| Light source cap-type | Welding | | |
| (or other electric interface) | | | |
| Mains or non-mains: | MLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | No |

Product parameters

| Parameter | | Value | Parameter | Value |
|--------------------------------------|--|---------------------------|--|--------------|
| | General product parameters: | | | |
| | mption in on- 100 h), rounded st integer | 10 | Energy efficiency class | F |
| indicating if it r in a sphere (3 | us flux (фuse), efers to the flux 60º), in a wide n a narrow cone | 1 000 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000 |
| On-mode pexpressed in W | oower (P _{on}), | 9,5 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 |
| for CLS, expres | dby power (P _{net}) ssed in W and second decimal | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 80 |
| Outer | Height | 12 | Spectral power | See image |
| dimensions | Width | 35 | distribution in the | in last page |
| without | Depth | 50 | | |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | | range 250 nm to 800 nm, at full-load | |
|---|----------------------|---|----------------|
| Claim of equivalent power ^(a) | Yes | If yes, equivalent power (W) | 72 |
| | | Chromaticity coordinates (x and y) | 0,380 0,380 |
| Parameters for LED and OLED I | ight sources: | | |
| R9 colour rendering index value | e 6 | Survival factor | 1,00 |
| the lumen maintenance factor | 0,96 | | |
| Parameters for LED and OLED I | nains light sources: | | |
| displacement factor (cos φ1) | 0,70 | Colour consistency in McAdam ellipses | 6 |
| Claims that an LED light source replaces a fluorescentight source without integrated ballast of a particular wattage. | t I | If yes then replacement claim (W) | - |
| Flicker metric (Pst LM) | 1,0 | Stroboscopic effect metric (SVM) | - |

(a)'-': not applicable;

(b)_{'-'} : not applicable;

