Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: LUTEC EUROPE NV, Herentalsebaan 425, 2160 Wommelgem, BE

_	•			
Type	Λt	liaht	COLL	rca.
IVDE	VI.	HEIIL	3 Uui	LC.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	Welding		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Parameter		Value	Parameter	Value		
	General product parameters:					
	mption in on- 100 h), rounded st integer	10	Energy efficiency class	F		
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	1 000 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode pexpressed in W	oower (P _{on}),	10,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80		
Outer	Height	12	Spectral power	See image		
dimensions	Width	35	distribution in the	in last page		
without	Depth	50		Page 1 / 3		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load			
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	72		
		Chromaticity coordinates (x and y)	0,440 0,403		
Parameters for LED and OLED	ight sources:	,			
R9 colour rendering index value	6	Survival factor	1,00		
the lumen maintenance factor	0,96				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		If yes then replacement claim (W)	-		
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	1,0		

(a)'-': not applicable;

(b)_{'-'} : not applicable;

