



## Type of luminaire

Type of luminaire	Wall luminaire.
Photometric body	Double-sided light facing up and down.
Characteristics of the luminaire	A luminaire with a wide range of applications, among others for lighting: wall and facade surfaces and other architectural concepts

## General information

Materials	Powder painted aluminum cast. Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket. EPDM cable gland.
Mounting method	Mounting of the luminaire: intermediate plate 2 adjustment holes 5x10mm, spacing 45mm, directly 2 holes ø5mm, spacing 68mm
Terminal	Connection terminals: max 3x2.5mm <sup>2</sup> , Possibility to connect the luminaire in loops, max 3x1.5mm <sup>2</sup> , Round tire cable with a diameter of ø7 ... 10.5mm
Type of light source	E27 lamp
Net / gross weight of luminaire	2,35kg / 2,35kg
Box dimensions [cm]	34x17x15

## Technical data

E27 lamp	QA55 / LED A55..60
Light source wattage	max 57W / LED 9W

This product contains light source of energy efficiency class **A+ D**

It is possible to order the luminaire with the E27 LED lamp type Philips Master LEDbulb 806lm / 8.5W / 2700K (dimmable)

## Accessories sold separately

46999021	LED E27 lamp
----------	--------------

## Recommended light sources

Osram LED Parathom Classic E27	Philips Master LEDbulb / Ledbulb Classic E27
Osram ECO PRO Classic 57<=>75W E27	Philips ECO Classic 53<=>75W E27

## Spare parts

08120006	Gasket.
----------	---------

## Files to download

Photometric LDT files	Photometric IES files
Manual	BIM ArchiCAD

## Indexes

Index	Color	RAL
120AL	ALUMINIUM	9006
120B	BLACK	9005
120GR	GRAPHITE	7016
120W	WHITE	9003