



Type of luminaire

Type of luminaire	Bollard.
Photometric body	Uncovered, diffused light with rotationally symmetrical light distribution.
Characteristics of the luminaire	A bollard luminaire with a stable and durable structure. For lighting private areas and public areas

General information

Materials	Hot-dip galvanized steel. Hot-dip galvanized and powder-coated steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes $\varnothing 9\text{mm}$ on a diameter of $\varnothing 65\text{mm}$ every 120° . Other accessories must be purchased separately
Terminal	Connection terminals: max $3 \times 2.5\text{mm}^2$, possibility to connect the luminaire in loops, max $3 \times 1.5\text{mm}^2$. Round insulated cable with a diameter of max $\varnothing 12.5\text{mm}$
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	9,23kg / 11,02kg
Box dimensions [cm]	20,5x20,5x91

Technical data

LED module	Lumens EDC 47C 10W xxx 230V A Ver.1.2 (Datasheet)
External control	Dimmers Lumens LED AC (User manual)
Luminaire wattage	10W
Lamp luminous flux	1098lm
Luminaire luminous flux	333lm
Efficiency of the luminaire	33,3lm/W
ULOR	50%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>50 000h
LED photobiological threat	RG0 or RG1
Power Factor luminaire	PF > 0,98
THD factor	< 20%
Ta Rated temperature	+25°C
Max ambient temperature	-35...+25°C

This product contains light source of energy efficiency class **A++**

Inrush current	43mA / 60ms
----------------	-------------

Accessories sold separately

205ZX0010	Concreting anchor
206GA0010	Ground anchor

Spare parts

06295000	Lens.
08295000	Gasket.
ZS1265zx0012	Service set.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
1265B	BLACK	9005
1265GA	GALVANIZED	-