



Type of luminaire

Type of luminaire	Wall luminaire.
Photometric body	Double-sided light facing up and down.
Characteristics of the luminaire	A luminaire with a wide range of applications, for illuminating wall and facade surfaces and other architectural concepts

General information

Materials	Powder painted aluminum cast. Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket. EPDM cable gland.
Mounting method	Fixing the luminaire: intermediate plate, 2 adjustment holes 5x10mm, spacing 45mm, directly 2 holes ø5mm, spacing 68mm.
Terminal	Connection terminals: max 3x2,5mm ² , possibility to connect luminaire in loop max 3x1.5mm ² . Round insulated cable with a diameter of ø7...10,5mm.
Type of light source	LED module, power supply
Light control	Trailing edge dimming
Box dimensions [cm]	34,5x15x17

Technical data

4 LED modules.	Philips Strip OC 0.5ft 550lm 8xx FC LV5 (Datasheet)
Driver	Philips Xitanium 14W 0,35A 40V TE SC 230V (Datasheet)
Light source wattage	11,6 W
Luminaire wattage	13,7 W
Lamp luminous flux	2043lm
Luminaire luminous flux	1280lm
Light source efficiency	176,1lm/W
Efficiency of the luminaire	93,4lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>70 000h
LED photobiological threat	RG0 or RG1
Power Factor luminaire	PF > 0,95
THD factor	< 20%
Ta Rated temperature	+25°C

This product contains light sources of energy efficiency class **A++**

Inrush current	1,87A/48µs
----------------	------------

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM Revit
BIM ArchiCAD	

Indexes

Index	Color	RAL
1306AL	ALUMINIUM	9006
1306B	BLACK	9005
1306GR	GRAPHITE	7016
1306W	WHITE	9003