



Type of luminaire

Type of luminaire	Accessories
Photometric body	Single-sided, symmetric light facing down.
Characteristics of the luminaire	Pole luminaire with 2160mm high (two-part luminaire). For lighting private areas, public spaces and other architectural concepts.

General information

Materials	Extruded aluminum profile, powder coated. Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket.
Mounting method	Fixing of the luminaire: 4 holes on a diameter ϕ 12mm, spacing 200x200mm. Art. 1360: 2-parts pole luminaire. Other accessories need to be purchased separately.
Terminal	Connection terminals: max 3x2,5mm ² , possibility to connect luminaire in loop max 3x2,5mm ² . A round wire in the isolation with a diameter of max ϕ 12,5mm.
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	10,54kg / 12,11kg
Box dimensions [cm]	25x115x56
Side area of luminaire	0,232m ²

Technical data

2 LED modules	Lumens LNM/280X30/9W/830/230V
External control	Dimmers Lumens LED AC (User manual)
Light source wattage	18W
Luminaire wattage	18W
Lamp luminous flux	1710lm
Luminaire luminous flux	962lm
Light source efficiency	95lm/W
Efficiency of the luminaire	53,4lm/W
ULOR	0%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Power Factor luminaire	PF > 0,99
THD factor	< 20%
Ta Rated temperature	+25°C
Max ambient temperature	-30...+25°C

This product contains light sources of energy efficiency class **A+**

Inrush current	108,8mA/500 μ s
----------------	---------------------

Accessories sold separately

116ZX0009	Concreting anchor (anchor L190mm).
117GA0009	Ground anchor.
118GA0009	Anchoring support.
119ZX0009	Concreting anchor (anchor L700mm).
7666ZX0009	Connection box with fuse 5x20mm

Spare parts

06136000	Lens.
08136000	Gasket.
ZS1360zx0010	Service set.

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM Revit
BIM ArchiCAD	



Indexes

Index	Color	RAL
1360AL	ALUMINIUM	9006
1360B	BLACK	9005
1360GR	GRAPHITE	7016