



Type of luminaire

Type of luminaire	Wall luminaire.
Photometric body	Double-sided light facing up and down.
Characteristics of the luminaire	Wall-mounted luminaire with modern design. For lighting private areas and public spaces.

General information

Materials	Base - galvanized steel. Front - galvanized steel or powder coated galvanized steel. Lens - safety glass, transparent. Silicone gasket.
Mounting method	Fixing of the luminaire: 2 holes \varnothing 4,2mm, spacing 45mm.
Terminal	Connection terminals: max 3x2,5mm ² , possibility to connect luminaire in loop max 3x1,5mm ² . A round wire in the isolation with a diameter of \varnothing 7...10,5mm.
Type of light source	LED Gu10 lamp, 25D
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	1,45kg / 1,45kg
Box dimensions [cm]	20x13x9,5

Technical data

2 LED GU10 lamps.	Philips Master LED ExpertColor 25D 3,9W=> 35W Gu10
Light source wattage	7,8W
Luminaire wattage	7,8W
Lamp luminous flux	530lm
Luminaire luminous flux	500lm
Light source efficiency	67,9lm/W
Efficiency of the luminaire	64,1lm/W
Color temperature	2700K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	97
Rated life time L70/B50 at 25°C	40 000h
Power Factor luminaire	PF 0,8
Ta Rated temperature	+25°C

This product contains light sources of energy efficiency class **A+**

Recommended light sources

Osram LED Parathom Advanced / Pro max 4W PAR16 Gu10 Philips Master LED max 4W PAR16 Gu10

Spare parts

46102507 LED Gu10 lamp.

Files to download

Photometric LDT files Photometric IES files
Manual BIM ArchiCAD

Indexes

Index	Color	RAL
1370B	BLACK	9005
1370GA	GALVANIZED	-