



## Type of luminaire

Type of luminaire	Wall luminaire.
Photometric body	Double-sided light facing up and down.
Characteristics of the luminaire	Wall-mounted luminaire with modern design. For lighting private areas and public spaces.

## General information

Materials	Base - galvanized steel. Front - galvanized steel or powder coated galvanized steel. Lens - safety glass, transparent. Silicone gasket.
Mounting method	Fixing of the luminaire: 2 holes $\varnothing 4,2$ mm, spacing 45mm.
Terminal	Zaciski podłączeniowe: max 3x2,5mm <sup>2</sup> , możliwość podłączenia oprawy w pętlę max 3x1,5mm <sup>2</sup> . Przewód w oponie okrągłej o średnicy $\varnothing 7...10,5$ mm.
Type of light source	LED GU10 lamp
Net / gross weight of luminaire	0,94kg / 1,35kg
Box dimensions [cm]	20x13x10

## Technical data

2 LED GU10 lamps.	LED PAR16
Light source wattage	2 x max 4W
Lamp luminous flux	2 X ~ 265lm
Ta Rated temperature	+25°C

This product contains light sources of energy efficiency class **A+**

Possibility to order luminaire with LED GU10 lamp type Philips Master LED ExpertColor 256lm/3,9W/2700K/25D (dimmable).

## Accessories sold separately

46102507

## Recommended light sources

Osram LED Parathom Advanced / Pro max 4W PAR16 GU10 Philips Master LED max 4W PAR16 GU10

## Files to download

Photometric LDT files	Photometric IES files
Manual	BIM ArchiCAD

## Indexes

Index	Color	RAL
1371B	BLACK	9005
1371BC	BLACK/COPPER	-
1371GA	GALVANIZED	-