



Type of luminaire

Type of luminaire	Wall luminaire.
Photometric body	Single-sided, symmetric light facing down.
Characteristics of the luminaire	Wall-mounted luminaire with modern design. For lighting private areas and public spaces.

General information

Materials	Base - galvanized steel. Front - galvanized steel or powder coated galvanized steel. Lens - safety glass, transparent. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: 2 holes $\varnothing 4,2\text{mm}$, spacing 45mm.
Terminal	Connection terminals: max $3 \times 2,5\text{mm}^2$, possibility to connect luminaire in loop max $3 \times 1,5\text{mm}^2$. A round wire in the isolation with a diameter of $\varnothing 7 \dots 10,5\text{mm}$.
Type of light source	LED Gu10 lamp
Net / gross weight of luminaire	0,85kg / 0,93kg
Box dimensions [cm]	12,5x13x10

Technical data

LED GU10 lamp	LED PAR16
Light source wattage	MAX 4W
Lamp luminous flux	~ 265lm
Light source efficiency	66,3lm/W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+**

Possibility to order luminaire with LED GU10 lamp type Philips Master LED ExpertColor 256lm/3,9W/2700K/25D (dimmable).

Accessories sold separately

46102507	LED GU10 lamp.
----------	----------------

Recommended light sources

Osram LED Parathom Advanced / Pro max 4W PAR16 Gu10 Philips Master LED max 4W PAR16 Gu10

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM ArchiCAD

Indexes

Index	Color	RAL
1374B	BLACK	9005
1374GA	GALVANIZED	-