



## Type of luminaire

Type of luminaire	Bollard.
Photometric body	Light with rotationally symmetrical light distribution.
Characteristics of the luminaire	Modern design luminaire. For lighting gardens, private areas and public spaces.

## General information

Materials	Powder painted aluminum cast. Lens - satin PMMA plastic. Silicone gasket. Nylon6 cable gland.
Mounting method	Fixing of the luminaire: 3 holes $\varnothing 9\text{mm}$ on a diameter $\varnothing 65\text{mm}$ every $120^\circ$ .
Terminal	Connection terminals: max $2 \times 2,5\text{mm}^2$ , possibility to connect in loop max $2 \times 2,5\text{mm}^2$ . A round wire in the isolation with a diameter of $\varnothing 8...12,5\text{mm}$ .
Type of light source	E27 lamp
Net / gross weight of luminaire	4,75kg / 5,73kg
Box dimensions [cm]	16x16x93

## Technical data

E27 lamp	QA55 / LED A55..60
Light source wattage	MAX 46W / LED 9W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+ D**

Possibility to order the luminaire with LED E27 Philips Master LEDbulb 806lm / 8,5W / 2700K (dimmable). The attached photometric test results apply to the luminaire, where the above-mentioned E27 LED lamp was mounted.

## Accessories sold separately

205ZX0010	Concreting anchor.
206GA0010	Ground anchor.
206GA0S10	Anchoring support.
46999021	LED E27 lamp.

## Recommended light sources

Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27
Osram LED Parathom Classic / Retrofit E27	Philips Master LEDbulb / Classic / CorePro E27

## Files to download

Photometric LDT files	Photometric IES files
Manual	

## Indexes

Index	Color	RAL
1380AL	ALUMINIUM	9006
1380GR	GRAPHITE	7016