



Type of luminaire

| | |
|----------------------------------|---|
| Type of luminaire | Bollard. |
| Photometric body | Light with rotationally symmetrical light distribution, covered from the top. |
| Characteristics of the luminaire | Bollard luminaire of stable and durable construction. For lighting private areas and public spaces. |

General information

| | |
|---------------------------------|---|
| Materials | Wood - scandinavian painted pine and hot-dip galvanized steel. Wood - scandinavian painted pine, hot-dip galvanized and powder painted steel. Lens - plastic PMMA in milky color. Silicone gasket. |
| Mounting method | Fixing of the luminaire: 3 holes $\varnothing 9\text{mm}$ with a diameter of $\varnothing 65\text{mm}$ every 120° . |
| Terminal | Connection terminals: max $3 \times 2,5\text{mm}^2$, possibility to connect luminaire in loop max $3 \times 1,5\text{mm}^2$. A round wire in the isolation with a diameter of max $\varnothing 12,5\text{mm}$. |
| Type of light source | E27 lamp |
| Net / gross weight of luminaire | 6,75kg / 8,15kg |
| Box dimensions [cm] | 20x20x91 |

Technical data

| | |
|----------------------|--------------------|
| E27 lamp | QA55 / LED A55..60 |
| Light source wattage | MAX 46W / LED 9W |
| Ta Rated temperature | +25°C |

This product contains light source of energy efficiency class **A+ D**

Possibility to order the luminaire with LED E27 Philips Master LEDbulb 806lm / 8,5W / 2700K (dimmable).

Accessories sold separately

| | |
|-----------|--------------------|
| 205ZX0010 | Concreting anchor. |
| 206GA0010 | Ground anchor. |
| 206GA0S10 | Anchoring support. |

Recommended light sources

Osram LED Parathom Classic E27 Philips Master LEDbulb / Ledbulb Classic E27

Spare parts

| | |
|----------|---------|
| 06281004 | Lens. |
| 08288002 | Gasket. |

Files to download

Photometric LDT files Photometric IES files
Manual

Indexes

| Index | Color | RAL |
|--------|------------|------|
| 1420B | BLACK | 9005 |
| 1420GA | GALVANIZED | - |