



## Type of luminaire

Type of luminaire	Bollard.
Photometric body	Light with rotationally symmetrical light distribution, covered from the top.
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces.

## General information

Materials	Wood - scandinavian impregnated pine and hot-dip galvanized steel. Wood - scandinavian impregnated pine, hot-dip galvanized and powder painted steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes $\varnothing$ 9mm with a diameter of $\varnothing$ 65mm every 120°.
Terminal	Connection terminals: max 3x2,5mm <sup>2</sup> , possibility to connect luminaire in loop max 3x1,5mm <sup>2</sup> . A round wire in the isolation with a diameter of max $\varnothing$ 12,5mm.
Type of light source	E27 lamp
Net / gross weight of luminaire	6,75kg / 8,15kg
Box dimensions [cm]	20x20x91

## Technical data

E27 lamp	QA55 / LED A55..60
Light source wattage	MAX 46W / LED 9W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+ D**

Possibility to order the luminaire with LED E27 Philips Master LEDbulb 806lm / 8,5W / 2700K (dimmable).

## Accessories sold separately

205ZX0010	Concreting anchor.
206GA0010	Ground anchor.
206GA0S10	Anchoring support.

## Recommended light sources

Osram LED Parathom Classic E27      Philips Master LEDbulb / Ledbulb Classic E27

## Spare parts

06281004	Lens.
08288002	Gasket.

## Files to download

Photometric LDT files      Photometric IES files  
Manual

## Indexes

Index	Color	RAL
1423B	BLACK	9005
1423GA	GALVANIZED	-