




Stockholm 1433XX0010 23.07.2021 v.10.2 www.norlys.com









Type of luminaire		
Type of lumianire	Bollard.	
Photometric body	Uncovered light with rotationally symmetrical light distribution.	
Characteristics of the luminaire	A bollard luminaire with a stable and durable structure. For lighting private areas and public areas	

General information			
Materials	Wood - scandinavian impregnated pine and hot-dip galvanized steel. Wood - scandinavian impregnated pine, hot-dip galvanized and powder painted steel. Lens - plastic PMMA in milky color. Silicone gasket.		
Mounting method	Fixing of the luminaire: 3 holes ø9mm with a diameter of ø65mm every 120 °.		
Terminal	Connection terminals: max 3x2.5mm², possibility to connect the luminaire in loops, max 3x1.5mm². Cable in a round wire with a maximum diameter of ø12.5mm		
Type of light source	E27 lamp		
Net / gross weight of luminaire	5,35kg / 6,35kg		
Box dimensions [cm]	20x20x55		

Technical data	
E27 lamp	QA55 / LED A5560
Light source wattage	MAX 46W / LED 9W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class A+ D

Possibility to order the luminaire with LED E27 Philips Master LEDbulb 806lm / 8,5W / 2700K (dimmable).

Accessories sold separately		
205ZX0010	Concreting anchor.	
206GA0010	Ground anchor.	
206GA0S10	Anchoring support.	

Recommended light sources

Osram LED Parathom Classic E27 Philips Master LEDbulb / Ledbulb Classic E27

Spare parts		
06281004	Lens.	
08288002	Gasket.	

Files to download

Photometric LDT files Photometric IES files

Manual

Indexes		
Index	Color	RAL
1433B	BLACK	9005
1433GA	GALVANIZED	-







