



Type of luminaire

Type of luminaire	Bollard.
Photometric body	Uncovered light, partly covered from the top.
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces.

General information

Materials	Hot-dip galvanized steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes $\varnothing 9\text{mm}$ with a diameter of $\varnothing 65\text{mm}$ every 120° .
Terminal	Connection terminals: max $3 \times 2,5\text{mm}^2$, possibility to connect luminaire in loop max $3 \times 2,5\text{mm}^2$. A round wire in the isolation with a diameter of max $\varnothing 12,5\text{mm}$.
Type of light source	E27 lamp
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	7,88kg / 8,52kg
Box dimensions [cm]	15,5x15,5x55

Technical data

E27 lamp	Philips Master LEDbulb A60 8,5W \leftrightarrow 60W E27
Light source wattage	8,5W
Luminaire wattage	8,5W
Lamp luminous flux	$\sim 806\text{lm}$
Luminaire luminous flux	252lm
Efficiency of the luminaire	29,6lm/W
Colour consistency (McAdam ellipse)	SDCM6
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	25 000h
Power Factor luminaire	PF 0,70
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+**

Accessories sold separately

205ZX0010	Concreting anchor.
206GA0010	Ground anchor.
206GA0S10	Anchoring support.

Recommended light sources

Osram LED Parathom Classic / Retrofit E27 Philips Master LEDbulb / Classic / CorePro E27

Spare parts

06295000	Lens.
08295000	Gasket.
46999021	LED E27 lamp.

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM ArchiCAD

Indexes

Index	Color	RAL
1488B	BLACK	9005
1488GA	GALVANIZED	-
1488GR	GRAPHITE	7016