




Grimstad 1546XX0010 23.07.2021 v.10.3 www.norlys.com





Type of luminaire		
Type of lumianire	Recessed wall luminaire.	
Photometric body	Diffused, uncovered light.	
Characteristics of the luminaire The luminaire is suitable for lighting stairs, steps, staircases, pathways, a other places		

	other places	
General information		
Materials	Powder painted aluminum cast. Lens - safety glass, milky colour. Silicone gasket. EPDM cable gland.	
Mounting method	Mounting of the luminaire: embedded in the wall - hole 258x112x115, fixing in a layered wall - hole 235x96x82	
Terminal	Connection terminals: max 3x2.5mm², Possibility to connect the luminaire in loops, max 3x1.5mm². Round insulated cable with a diameter of ø7 10.5mm	
Type of light source	E14 lamp	
Net / gross weight of luminaire	1,44kg / 1,6kg	
Box dimensions [cm]	27x12,5x11,5	

Technical data		
E14 lamp	QB35	
Light source wattage	max 46W / LED 6W	

This product contains light source of energy efficiency class A+ D

Recommended light sources

Osram LED Parathom Retrofit/Advanced/ Classic B38 E14 Philips Master LED luster/candle/frosted B38 E14
Osram ECO PRO Classic 46<=>60W QB35 E14 Philips ECO Classic 42<=>60W QB35 E14

Spare parts

 06152000
 Lens.

 08154000
 Gasket.

Files to download

Manual

Indexes		
Index	Color	RAL
1546AL	ALUMINIUM	9006
1546GR	GRAPHITE	7016





