

滥

Rena 1552XX0014 23.07.2021 v.14.6 www.norlys.com







Type of luminaire	
Type of lumianire	In-ground luminaire.
Photometric body	Uncovered light.
Characteristics of the luminaire	An orientation luminaire that can be driven on by vehicles with pneumatic tires. Luminaires should not be used on traffic lanes where they would be exposed to horizontal weight load as a result of sudden braking, acceleration, and change of direction. The light direction angle can be adjusted, up to a maximum of 10 degrees

General information		
Materials	Powder painted aluminum cast. Front - stainless steel. Lens - safety glass, transparent. Silicone gasket. Nickel plated brass cable gland.	
Mounting method	Fixing of the luminaire: 3 holes ø4,5mm on a diameter ø100mm every 120° connected to the assembly box, or to appropriately prepared hole in the wood (see manual). Other accessories sold separately	
Terminal	The luminaire is equipped with a cable type 05RN8-F 3G1 with a length of 3m. To be connected in a properly selected installation box. The maximum load of the luminaire is 2000 kg. Note: on the glass surface in the middle work point, operating temperatures are in accordance with the standard 60598 (ambient temperature 15°C)	
Type of light source	LED Gu10 lamp	
Net / gross weight of luminaire	1,01kg / 1,21kg	
Box dimensions [cm]	15,6x15,6x19,4	

Technical data	
Light source wattage	max 6W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class A+

It is possible to order the luminaire with the LED Gu10 lamp type Philips Master LED ExpertColor 5,5W <=> 50W PAR16 Gu10 375lm / 800cd / 3000K / 36D (dimmable). To the luminaire, in order to obtain light covered from above, a round diaphragm cover, can be mounted art.140xx0009

Accessories sold separately	
143ZX0009	Power cord cover
145ZX0009	Hermetic 3-track box
146ZX0009	Hermetic 8-track box
46102506	LED Gu10 lamp

Recommended light sources

Osram LED Parathom max 6W <=> 50W PAR16 Gu10 Philips Master LED max 6W<=>50W PAR16 Gu10

Spare parts	
06155000	Lens.
08155001	Gasket.

Files to download

Photometric LDT files Photometric IES files

Manual BIM ArchiCAD

Indexes		
Index	Color	RAL
1552ST	STAINLESS STEEL	-





