## Pobrano z mamadecor.pl

Arendal 1560XX0012 23.07.2021 v.12.7 www.norlys.com

#### ARENDAL 1560 IP 55⁄65 EHE CE 220-240V 50-60Hz E27

Type of luminaire	Type of luminaire	
Type of lumianire	Bollard.	
Photometric body	Uncovered light.	
Characteristics of the luminaire	Modern design luminaire with a combination of decorative crystal lampshade and durable and stable casing	
General information		
Materials	Hot-dip galvanized and powder-coated steel. Lens - crystal glass, satin inside. Lens may change to light amber colour over time.	
Mounting method	Fixing of the luminaire: 3 holes ø9mm with a diameter of ø65mm every 120°.	
Terminal	Connection terminals: max 3x4mm², possibility to connect luminaire in loop max 3x2,5mm². Round insulated cable with a diameter of max ø12,5mm.	
Type of light source	E27 lamp	
Net / gross weight of luminaire	14,26kg / 15,71kg	
Box dimensions [cm]	97x18,5x18,5	
Technical data		
E27 lamp	QA55 / LED A5560	

E27 lamp	QA55 / LED A5560
Light source wattage	max 46W / LED 9W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class A+

Possibility to order the luminaire with LED E27 Philips Master LEDbulb 806lm / 8,5W / 2700K (dimmable).

Accessories sold separately		
205ZX0010	Concreting anchor	
206GA0010	Ground anchor	
206GA0S10	Anchoring support	
46999021	LED E27 lamp	

#### Recommended light sources

Osram LED Parathom Classic E27 Osram ECO PRO Classic 46<=>60W E27

Lens

Philips Master LEDbulb / Ledbulb Classic E27 Philips ECO Classic 42<=>60W E27

### Spare parts

# 915600229

Files to download

Manual

Indexes		
Index	Color	RAL
1560B	BLACK	9005
1560GA	GALVANIZED	-
1560GR	GRAPHITE	7016



NORLYS

146

850

120 120





