



Type of luminaire

Type of luminaire	Wall luminaire.
Photometric body	Diffused, uncovered light.
Characteristics of the luminaire	Scandinavian design luminaire. For lighting gardens, private areas and public spaces.

General information

Materials	Base - powder painted aluminum cast. Front - hot-dip galvanized steel, powder painted steel. Lens - milky polycarbonate, UV stabilized. Silicone gasket.
Mounting method	Fixing of the luminaire: 2 holes \varnothing 5mm, spacing 80x80mm.
Terminal	Fixing of the luminaire: max. $3 \times 2,5\text{mm}^2$, possibility to connect luminaire in loop max. $3 \times 1,5\text{mm}^2$. A round wire in the isolation with a diameter $\varnothing 7 \dots 10,5\text{mm}$.
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	2,7kg / 2,85kg
Box dimensions [cm]	21,5x14x24

Technical data

LED module	Lumens EDC 57C 8W xxx 230V A FF Ver.1.0 (Datasheet)
Light source wattage	8W
Luminaire wattage	8W
Lamp luminous flux	890lm
Luminaire luminous flux	332lm
Light source efficiency	111,3lm/W
Efficiency of the luminaire	41,5lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
LED photobiological threat	RG0 or RG1
Power Factor luminaire	PF > 0,99
THD factor	< 20%
Ta Rated temperature	+25°C
Max ambient temperature	-35...+25°C

This product contains light source of energy efficiency class **A+**

Inrush current	2,9A/34 μ s
----------------	-----------------

Spare parts

06220000	Lens.
08550005	Gasket.
46999552	LED module.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
1600B	BLACK	9005
1600GA	GALVANIZED	-