







44

E27

ASKER 1702

CE

EAC

Type of luminaire				
Type of lumianire	Wall luminaire.			
Photometric body	Double-sided light facing up and down.			
Characteristics of the luminaire	Luminaire with a wide range of applications for example for illumination of wa and facade surfaces or any other architectural concepts.			
General information				
Materials	Base - powder painted aluminum cast. Body - hot-dip galvanized steel Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket.			
Mounting method	Fixing of the luminaire: 2 holes ø4,5mm, spacing 180x60mm.			
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in loop max 3x1,5mm². A round wire in the isolation with a diameter of ø710,5mm.			
Type of light source	E27 lamp			
Net / gross weight of luminaire	1,45kg / 1,6kg			
Box dimensions [cm]	24x12x9,5			
Technical data				
E27 lamp	QA55 / LED A5560			
I tale a successive successive				

Light source wattage max 46W / LED 9W +25°C Ta Rated temperature

This product contains light source of energy efficiency class A+

Possibility to order the luminaire with LED E27 Philips Master LEDbulb 806lm / 8,5W / 2700K (dimmable).

Accessories sold

46999021	LED E27 lamp.		

Recommended light sources

Osram LED Parathom Classic E27			
Osram ECO PRO Classic 46<=>60W E27			

Philips Master LEDbulb / Ledbulb Classic E27 Philips ECO Classic 42<=>60W E27

Pobrano z mamadecor.pl

Asker 1702XX0010 23.07.2021 v.10.4 www.norlys.com

Files to download

i neo to dominoda			
Photometric LDT files		Photometric IES files	
Manual		BIM Revit	
BIM ArchiCAD			
Indexes			
Index	Color	RAL	
1702GA	GALVANIZED	-	



