





Asker 1707XX0010 23.07.2021 v.10.4 www.norlys.com



] [

85	215





Type of luminaire		
Type of lumianire	Wall luminaire.	
Photometric body	Single-sided light facing down.	
Characteristics of the luminaire	Luminaire with a wide range of applications for example for illumination of walls and facade surfaces or any other architectural concepts.	

General information	
Materials	Base - powder painted aluminum cast. Body - hot-dip galvanized steel Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket.
Mounting method	Fixing of the luminaire: 2 holes ø4,5mm, spacing 180x60mm.
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in loop max 3x1,5mm². A round wire in the isolation with a diameter of ø710,5mm.
Type of light source	E27 lamp
Box dimensions [cm]	24x12x9,5

Technical data		
E27 lamp	QA55 / LED A5560	
Light source wattage	max 46W / LED 9W	
Ta Rated temperature	+25°C	

This product contains light source of energy efficiency class A+ D

Possibility to order the luminaire with LED E27 Philips Master LEDbulb 806lm / 8,5W / 2700K (dimmable).

Accessories sold separately	
46999021	LED E27 lamp.

Recommended light sources		
Osram LED Parathom Classic E27	Philips Master LEDbulb / Ledbulb Classic E27	
Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27	

Files to download		
Photometric LDT files	Photometric IES files	
Manual	BIM Revit	
BIM ArchiCAD		

Indexes		
Index	Color	RAL
1707GA	GALVANIZED	-





