



## Type of luminaire

Type of luminaire	Recessed wall luminaire.
Photometric body	Covered light facing down.
Characteristics of the luminaire	The luminaire is adapted to illuminate stairs, steps, staircases, communication pathways and other applications

## General information

Materials	Front - hot-dip galvanized steel. Body - powder painted aluminum cast Lens - safety glass, satin. Silicone gasket. EPDM cable gland.
Mounting method	Fixing the luminaire: embedded in the wall - hole 258x112x115, fixing in a sandwich wall - hole 235x96x82
Terminal	Connection terminals: max 3x2.5mm <sup>2</sup> , Possibility to connect the luminaire in loops, max 3x1.5mm <sup>2</sup> . Round insulated cable with a diameter of $\phi 7 \dots 10.5$ mm
Type of light source	LED module, power supply
Light control	Trailing edge dimming
Net / gross weight of luminaire	1,41kg / 1,6kg
Box dimensions [cm]	27x14x13

## Technical data

LED module	Philips Strip OC 0.5ft 550lm 8xx FC HV5 (Datasheet)
Driver	Philips Xitanium 7W 0,35A 20V TE SC 230V (Datasheet)
Light source wattage	3,9W
Luminaire wattage	5,2W
Lamp luminous flux	653lm
Luminaire luminous flux	295lm
Light source efficiency	167,4lm/W
Efficiency of the luminaire	56,7lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>70 000h
Power Factor luminaire	PF > 0,96
THD factor	20 %
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A++**

Inrush current	1A/15,2 $\mu$ s
----------------	-----------------

## Spare parts

ZS1933zx0011	LED module.
--------------	-------------

## Files to download

Photometric LDT files	Photometric IES files
Manual	

## Indexes

Index	Color	RAL
1933GA	GALVANIZED	-