



STOCKHOLM Heavy duty galvanized steel or galvanized and powder coated bollard with opal or clear polycarbonate lens.


| Art | Watt | Class | Type of light source: | Luminous flux | Colour temperature | Lifetime (L70/B50) | EEL | Lens | Height (cm) | Dimmable |
|------|------|-------|-----------------------|---------------|--------------------|--------------------|-------|---------------------|-------------|------------|
| 299 | - | II | E27 | - | - | - | A+..D | Opal polycarbonate | 28cm | - |
| 1269 | 8,5W | II | LED E27 | - | 2700K | 25 000h | A+ | Opal polycarbonate | 28cm | Dim. Triac |
| 1268 | 10W | I | LED | 294 lm | 3000K | 50 000h | A+ | Opal polycarbonate | 28cm | Dim. Triac |
| 289 | - | II | E27 | - | - | - | A+..D | Opal polycarbonate | 49cm | - |
| 298 | - | II | E27 | - | - | - | A+..D | Clear polycarbonate | 49cm | - |
| 1469 | 8,5W | II | LED E27 | 294 lm | 2700K | 25 000h | A+ | Opal polycarbonate | 49cm | Dim. Triac |
| 1260 | 10W | I | LED | 294 lm | 3000K | 50 000h | A+ | Opal polycarbonate | 49cm | Dim. Triac |

Accessories for Stockholm


| | | |
|-----|-------------------|--------|
| 205 | Concreting anchor | p. 114 |
| 206 | Anchoring support | p. 114 |

Art. 1269, i 1469: 8,5W LED E27 included, 806 lm, 2700K, 25000h, dimmable, EEL: A+

* **Stockholm with 4000K** available by request, contact your supplier.



Art. 299
Art. 1269
Art. 1268



Art. 289
Art. 298
Art. 1469
Art. 1260