

Pobrano z mamadecor.pl


Halmstad 210XX0010 23.07.2021 v.10.4 www.norlys.com











| ΗA | 11/ | NS ⁻ | ΤA | D ź | 21 |
|----|---------------------|-----------------|----------|-----|----|
| CE | 220-240V 50-60Hz | | IP 65 | E27 | |

| Type of luminaire | e of luminaire | | |
|----------------------------------|---|--|--|
| Type of lumianire | Bollard. | | |
| Photometric body | Uncovered light, partly covered from the top. | | |
| Characteristics of the luminaire | Bollard luminaire of stable and durable construction. For lighting private areas and public spaces. | | |
| General information | neral information | | |

| Materials | Hot-dip galvanized steel. Lens - plastic PMMA in milky color. Silicone gasket. | |
|---------------------------------|--|--|
| Mounting method | Fixing of the luminaire: 3 holes ø9mm with a diameter of ø65mm every 120 °. | |
| Terminal | Connection terminals: max 2x2,5mm ² A round wire in the isolation with a diameter of max ø12,5mm. | |
| Type of light source | E27 lamp | |
| Net / gross weight of luminaire | 4,5kg / 4,79kg | |
| Box dimensions [cm] | 31,5x14x16 | |

Technical data

| rechnical uata | | | |
|--|------------------|--|--|
| E27 lamp | QA55 / LED A5560 | | |
| Light source wattage | MAX 46W / LED 9W | | |
| Ta Rated temperature | +25°C | | |
| This product contains light source of energy efficiency class A+ D | | | |

Possibility to order the luminaire with LED E27 Philips Master LEDbulb 806lm / 8,5W / 2700K (dimmable).

| Accessories sold separately | |
|-----------------------------|--------------------|
| 205ZX0010 | Concreting anchor. |
| 206GA0010 | Ground anchor. |
| 206GA0S10 | Anchoring support. |
| 46999021 | LED E27 lamp. |

Recommended light sources

| Osram LED Parathom Classic E27 | Philips Master LEDbulb / Ledbulb Classic E27 |
|------------------------------------|--|
| Osram ECO PRO Classic 46<=>60W E27 | Philips ECO Classic 42<=>60W E27 |

| 20° | Spare parts | | |
|-----|-------------|---------|--|
| 05° | 06295000 | Lens. | |
| | 08295000 | Gasket. | |
| | | | |

Files to download

| Photometric LDT files | 1 | Photometric IES files | |
|-----------------------|------------|-----------------------|--|
| Manual | | BIM ArchiCAD | |
| Indexes | | | |
| Index | Color | RAL | |
| 210B | BLACK | 9005 | |
| 210GA | GALVANIZED | - | |
| 210GR | GRAPHITE | 7016 | |
| | | | |



