



Type of luminaire

Type of luminaire	Bollard.
Photometric body	Uncovered light, partly covered from the top.
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces.

General information

Materials	Hot-dip galvanized steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes $\varnothing 9\text{mm}$ with a diameter of $\varnothing 65\text{mm}$ every 120° .
Terminal	Connection terminals: max $3 \times 2,5\text{mm}^2$. A round wire in the isolation with a diameter of max $\varnothing 12,5\text{mm}$.
Type of light source	E27 lamp
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	4,5kg / 4,79kg
Box dimensions [cm]	31,5x14x16

Technical data

E27 lamp	Philips Master LEDbulb A60 8,5W \leftrightarrow 60W E27
Light source wattage	LED 8,5W
Luminaire wattage	8,5W
Colour consistency (McAdam ellipse)	SDCM6
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	25 000h
Power Factor luminaire	PF>0,7
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+**

Accessories sold separately

205ZX0010	Concreting anchor.
206GA0010	Ground anchor.
206GA0S10	Anchoring support.

Recommended light sources

Osram LED Parathom Classic E27	Philips Master LEDbulb / Ledbulb Classic E27
Osram ECO PRO Classic 46 \leftrightarrow 60W E27	Philips ECO Classic 42 \leftrightarrow 60W E27

Spare parts

06295000	Lens.
08295000	Gasket.
0902100207	Electric set.

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM ArchiCAD

Indexes

Index	Color	RAL
212B	BLACK	9005
212GA	GALVANIZED	-
212GR	GRAPHITE	7016