





Stockholm 281XX0309 23.07.2021 v.09.3 www.norlys.com



Ø 350
max.2480 min.1510





Type of luminaire	pe of luminaire	
Type of lumianire	Accessories	
Photometric body	Uncovered light.	
Characteristics of the luminaire	Pole top luminaire in scandinavian design. For installation on a lighting pole with adjustable height 15102480mm. For lighting gardens, parks, and any other architectural concepts.	

	· ·	
General information		
Materials	Hot-dip galvanized steel. Powder painted steel. Lens - transparent plastic PMMA.	
Mounting method	Fixing of the luminaire: 3 holes Ø10,5 on a diameter Ø270mm every 120°. Set contains: art.2017- luminaire art. 3009/3011- lighting pole Other accessories need to be purchased separately.	
Terminal	Connection terminals: max 4x2,5mm², possibility to connect luminaire in loop max 4x2,5mm². A round wire in the isolation on diameter ø612,5mm.	
Type of light source	E27 lamp	

Technical data	
E27 lamp	QA55 / LED A5560
Light source wattage	max 77W / LED 9W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class A+ D

Recommended light sources		
Philips Master LEDbulb / Classic / CorePro E27	Osram ECO PRO Classic 77<=>100W E27	
Philips ECO Classic 70<=>100W E27	Philips Master LEDbulb / LEDbulb Classic E27	

Spare parts	Spare parts	
06281002	Lens.	
08281001	Gasket.	

Files to download

Photometric LDT files Photometric IES files

Manual

Indexes		
Index	Color	RAL
281B	BLACK	9005
281GA	GALVANIZED	-





