



## STOCKHOLM 284 CE III 220240V 500HZ III 154 E27


## Pobrano z mamadecor.pl

Stockholm 284XX0010 23.07.2021 v.10.1 www.norlys.com









L	50-60Hz 54 E27	www.norlys.co		
	Type of luminaire			
	Type of lumianire	Bollard.		
	Photometric body	Uncovered light.		
	Characteristics of the luminaire	Scandinavian design luminaire. For lighting gardens, terraces and any others architectural concepts.		
	General information			
	Materials	Hot-dip galvanized and powder-coated steel. Lens - transparent plastic PMMA. EPDM cable gland.		
	Mounting method	Fixing of the luminaire: using attached anchor, 2 holes ø7mm spacing 90mm. For mounting on a ground, wall, platform and other construction.		
	Terminal	Connection terminals: max 2x2,5mm². A round wire in the isolation with a diameter of max ø12mm.		
	Type of light source	E27 lamp		
	Technical data			
	E27 lamp	QA55 / LED A5560		
	Light source wattage	max 46W / LED 9W		
	This product contains light source of energy efficiency class A+ D			
	Recommended light sour	rces		
	Osram LED Parathom Classic E27	Philips Master LEDbulb / Ledbulb Classic E27		
	Osram ECO PRO Classic 46<=>60W	/ E27 Philips ECO Classic 42<=>60W E27		

## Spare parts

## 06280007 Lens 08280014

Indexes		
Index	Color	RAL
284B	BLACK	9005
284GA	GALVANIZED	-









Gasket. Files to download Photometric LDT files Photometric IES files Manual