














Como 373XX0309 23.07.2021 v.09.1 www.norlys.com









Type of luminaire	
Type of lumianire	Accessories
Photometric body	Uncovered light.
Characteristics of the luminaire Classic design luminaire, mounted on a telescopic lighting pole. Adjustable height 18202490mm. For lighting gardens, terraces and other architectural concepts.	

Powder painted aluminum cast. Lens - clear polycarbonate, UV stabilized. Silicone gasket.
Fixing of the luminaire: 3 holes ø10,5mm, on a daimeter ø240mm every 120°. Set contains: Art. 3030 - luminaire, Art. 3040 - reduction, Art. 3010 - lightning pole. Other accessories need to be purchased separately.
Connection terminal: max. 4x2,5mm², possibility to connect luminaire in loop max 4x2,5mm². A round wire in the isolation with a diameter of max ø612,5mm.
E27 lamp
12,31kg / 15,85kg

Technical data	
E27 lamp	QA55 / LED A5560
Light source wattage	3 x MAX 57W / LED 9W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class A+ D

Possibility to order the luminaire with LED E27 Philips Master LEDbulb 806lm / 8,5W / 2700K (dimmable).

Accessories sold separately		
108GA0009	Anchoring support.	
305ZX0009	Concreting anchor.	
306ZX0009	Ground anchor.	
46999021	LED E27 lamp.	

Recommended light sources				
Osram ECO PRO Classic 57<=>75W E27	Philips ECO Classic 53<=>75W E27			
Osram LED Parathom Classic / Retrofit E27	Philips Master LEDbulb / Classic / CorePro E27			

Spare parts	
06370797	Lens.

Files to download	
Photometric LDT files	Photometric IES files

Manual

Indexes		
Index	Color	RAL
373B	BLACK	9005
373W	WHITE	9003





