



## Type of luminaire

Type of luminaire	Bollard.
Photometric body	Light with rotationally symmetrical light distribution, covered from the top.
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces.

## General information

Materials	Hot-dip galvanized and powder-coated steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes $\varnothing 9\text{mm}$ with a diameter of $\varnothing 65\text{mm}$ every $120^\circ$ .
Terminal	Connection terminals: max $3 \times 4\text{mm}^2$ , possibility to connect luminaire in loop max $3 \times 2,5\text{mm}^2$ . A round wire in the isolation with a diameter of max $\varnothing 12,5\text{mm}$ .
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	9,3kg / 10,7kg
Box dimensions [cm]	20,5x20,5x91

## Technical data

LED module	Lumens EDC/57C/8W/840/230V/A011 FF
Light source wattage	8W
Luminaire wattage	8W
Lamp luminous flux	961lm
Light source efficiency	120,1lm/W
Color temperature	4000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Power Factor luminaire	PF > 0,99
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+**

Inrush current	57,4mA/500 $\mu\text{s}$
----------------	--------------------------

## Accessories sold separately

205ZX0010	Concreting anchor.
206GA0010	Ground anchor.
206GA0S10	Anchoring support.

## Spare parts

06291001	Lens.
08288004	Gasket.
46999553	LED module.

## Files to download

Photometric LDT files	Photometric IES files
Manual	BIM ArchiCAD

## Indexes

Index	Color	RAL
5021B	BLACK	9005
5021GA	GALVANIZED	-