



## Type of luminaire

Type of luminaire	Wall luminaire.
Photometric body	Single-sided light facing down.
Characteristics of the luminaire	A luminaire with a classic and simple design for general use

## General information

Materials	Hot-dip galvanized steel. Powder painted steel. Lens - satin polycarbonate, UV stabilized . EPDM cable gland.
Mounting method	Fixing the luminaire: 2 holes ø5.5mm, spacing 100mm
Terminal	Connection terminals: max 3x2.5mm <sup>2</sup> , Possibility to connect the luminaire in loops, max 3x1.5mm <sup>2</sup> . Round insulated cable with a diameter of ø7 ... 10.5mm
Type of light source	LED module, power supply
Light control	Trailing edge dimming
Net / gross weight of luminaire	1,05kg / 1,25kg
Box dimensions [cm]	17x16x29

## Technical data

LED module	Philips Strip 0.5ft 490lm 8xx FC HV5 (Datasheet)
Driver	Philips Xitanium 7W 0,35A 20V TE SC 230V (Datasheet)
Light source wattage	4W
Luminaire wattage	5,2W
Lamp luminous flux	681lm
Luminaire luminous flux	438lm
Light source efficiency	170,3lm/W
Efficiency of the luminaire	84,2lm/W
ULOR	0%
Color temperature	4000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>70 000h
LED photobiological threat	RG0 or RG1
Power Factor luminaire	PF>0,9
THD factor	< 20%
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A++**

Inrush current	1A / 15,2µs
----------------	-------------

## Maximum number of luminaires of this type per MCB:

**B 10A:** 157, **B 16A:** 250, **C 10A:** 260, **C 16A:** 425

## Spare parts

06163001	Lens.
4699100101	LED module.
46999746	Power supply.
950390302	Electric set.

## Files to download

Photometric LDT files	Photometric IES files
Manual	

## Indexes

Index	Color	RAL
5039B	BLACK	9005
5039GA	GALVANIZED	-
5039W	WHITE	9003