



## Type of luminaire

Type of luminaire	Wall luminaire.
Photometric body	Double-sided light facing up and down.
Characteristics of the luminaire	Luminaire with a wide range of applications for example for illumination of walls and facade surfaces or any other architectural concepts.

## General information

Materials	Powder painted aluminum cast. Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: aluminum plate with 2 holes 5x10mm spacing 45mm, or directly: 2 holes ø5mm spacing 68mm.
Terminal	Connection terminals: max 3x2,5mm <sup>2</sup> , possibility to connect luminaire in loop max 3x1,5mm <sup>2</sup> . A round wire in the isolation with a diameter of ø7...10,5mm.
Type of light source	LED module, power supply
Light control	Light control - DALI/TD system
Net weight of luminaire	2,27kg
Box dimensions [cm]	31,5x14x16

## Technical data

2 LED modules	Philips Strip 0.5ft 550lm 830 FC HV4
Light source wattage	8W
Luminaire wattage	10,2W
Lamp luminous flux	1296lm
Light source efficiency	162lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>70 000h
Power Factor luminaire	PF 0,88
Ta Rated temperature	+25°C

This product contains light sources of energy efficiency class **A++**

Inrush current	5A/45µs
----------------	---------

## Maximum number of luminaires of this type per MCB:

**B 10A:** 80, **B 16A:** 130, **C 10A:** 135, **C 16A:** 221

## Spare parts

08120006	Gasket.
46999609	LED module.
46999733	Power supply.

## Files to download

Manual BIM ArchiCAD

## Indexes

Index	Color	RAL
5093AL	ALUMINIUM	9006
5093B	BLACK	9005
5093GR	GRAPHITE	7016
5093W	WHITE	9003