



## Type of luminaire

Type of luminaire	Wall luminaire.
Photometric body	Single-sided light with 4° beam angle facing up.
Characteristics of the luminaire	Luminaire with a wide range of applications for example for illumination of walls and facade surfaces or any other architectural concepts

## General information

Materials	Powder painted aluminum cast. Lens - safety glass, transparent. Silicone gasket. EPDM cable gland.
Mounting method	Mounting of the luminaire: 2 holes ø7mm, spacing 100x80mm
Terminal	Connection terminals: max 3x2,5mm <sup>2</sup> , Possibility to connect luminaire in loop max 3x1,5mm <sup>2</sup> , A round wire in the isolation with a diameter of ø7...10,5mm
Type of light source	LED module, power supply
Light control	Non-dimmable luminaire
Net / gross weight of luminaire	4,57kg / 5,03kg
Box dimensions [cm]	20x17x28

## Technical data

LED module	Cree JK3030 no.1805004 (Datasheet)
Driver	Philips Xitanium 10W 0,5A 20V TE SC 230V (Datasheet)
Light source wattage	4,5W
Luminaire wattage	6,4W
Lamp luminous flux	641lm
Light source efficiency	142,4lm/W
Color temperature	4000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	72 000h
Power Factor luminaire	PF 0,90
THD factor	20%
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+**

Inrush current	3,36A/36µs
----------------	------------

## Maximum number of luminaires of this type per MCB:

**B 10A:** 126, **B 16A:** 200, **C 10A:** 208, **C 16A:** 340

## Spare parts

ZS5128zx0C09	Service set.
--------------	--------------

## Files to download

Photometric LDT files	Photometric IES files
Manual	BIM Revit
BIM ArchiCAD	

## Indexes

Index	Color	RAL
5128AL	ALUMINIUM	9006
5128GR	GRAPHITE	7016