



## Type of luminaire

|                                  |                                      |
|----------------------------------|--------------------------------------|
| Type of luminaire                | Wall/ceiling luminaire.              |
| Photometric body                 | Diffused, uncovered light.           |
| Characteristics of the luminaire | Modern design plafon type luminaire. |

## General information

|                         |  |
|-------------------------|--|
| Materials               | Powder painted aluminum cast. Lens - milky polycarbonate, UV stabilized. Silicone gasket. EPDM cable gland.  |
| Mounting method         | Fixing of the luminaire: 2 holes $\varnothing$ 5mm, spacing 165x95mm.  |
| Terminal                | Connection terminals: max $3 \times 2,5 \text{mm}^2$ , possibility to connect luminaire in loop max $3 \times 1,5 \text{mm}^2$ . A round wire in the isolation with a diameter of $\varnothing 6 \dots 10 \text{mm}$ . |
| Type of light source    | LED E27 lamp   |
| Net weight of luminaire | 1,49kg   |
| Box dimensions [cm]     | 26,5x26,5x11   |

## Technical data

|                      |             |
|----------------------|-------------|
| LED E27 lamp         | LED A55..60 |
| Light source wattage | max 9W      |
| Lamp luminous flux   | ~ 806lm     |

This product contains light source of energy efficiency class **A+**

Possibility to order luminaire with LED E27 lamp Philips Master LEDbulb 806lm / 8,5W / 2700K (dimnable).

## Recommended light sources

Osram LED Parathom Classic E27 Philips Master LEDbulb / Ledbulb Classic E27

## Spare parts

|          |               |
|----------|---------------|
| 06520002 | Lens.         |
| 08525000 | Gasket.       |
| 46999021 | LED E27 lamp. |

## Files to download

Photometric LDT files Photometric IES files  
Manual

## Indexes

| Index | Color     | RAL  |
|-------|-----------|------|
| 538AL | ALUMINIUM | 9006 |
| 538GR | GRAPHITE  | 7016 |