






Kiruna 597XX0009 23.07.2021 v.09.1 www.norlys.com





Type of luminaire				
Type of lumianire	Wall luminaire.			
Photometric body	Uncovered light, partly covered from the top.			
Characteristics of the luminaire	Luminaire with stable and durable construction. For use in private and public areas requiring high resistance to external mechanical damage.			
General information				
Materials	Powder painted aluminum cast. Lens - clear polycarbonate, UV stabilized. Silicone gasket. EPDM cable gland.			
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in loop max 3x1,5mm². A round wire in the isolation with a diameter ø710,5mm.			
Type of light source	E27 lamp			
Technical data				
E27 lamp	QA55 / LED A5560			
Light source wattage	MAX 46W / LED 9W			
Ta Rated temperature	+25°C			

This product contains	light source of	f energy efficiency class <b>l</b>	A+

Accessories sold separately	
46999021	LED E27 lamp.

Recommended light sources				
Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27			
Osram LED Parathom Retrofit/Advanced/ Classic B38 E14	Philips Master LED luster/candle/frosted B38 E14			

## Files to download

Manual

Indexes				
Index	Color	RAL		
597AL	ALUMINIUM	9006		
597GR	GRAPHITE	7016		





