




Type of luminaire

















Modern design luminaire mounted on a telescopic lighting pole with a cap Characteristics of the luminaire diameter Ø60mm. Other accessories have to be ordered separately. General information Powder painted aluminum cast. Lens - plastic PMMA in milky color. Silicone Materials

	gasket
Mounting method	Fixing of the luminaire: luminaire adjusted to ø60mm lighting pole, depth 95mm.
Terminal	H05RN-F 3G1 cable 6m long, for connection in an appropriately selected electrical installation box.
Type of light source	LED module, power supply
Light control	Non-dimmable luminaire
Side area of luminaire	0,042m ²

Technical data	
Driver durability	100000h
Light source wattage	27,2W
Luminaire wattage	32W
Lamp luminous flux	4180lm
Luminaire luminous flux	2996lm
Light source efficiency	153,7lm/W
Efficiency of the luminaire	93,6lm/W
ULOR	0%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>50 000h
LED photobiological threat	RG0 or RG1
Energy Efficiency Index	A++
Power Factor luminaire	PF 0,98
THD factor	9%
Overvoltage	6 / 10kV
Ta Rated temperature	+25°C
Max ambient temperature	-30+ 25°C
Inrush current	19A / 210µs

Maximum number of luminaires of this type per MCB:

B 10A: 20, B 16A: 32, C 10A: 32, C 16A: 54

Accessories sold separately , xx - color of the luminaire		
3004xx0009	Telescopic lighting pole with adjustable height 3600 4500mm, mounting cap Ø76	
3005xx0009	Telescopic lighting pole with adjustable height 3600 4500mm, mounting cap Ø76. Concreting anchor included.	
7661zx0009	Electric box	
7663zx0009	Concreting anchor	
7664ZX0009	100 kg concrete foundation for mounting lighting pole.	
7665xx0009	Reduction for Ø60 luminaire to install on Ø76 lighting pole.	

Spare parts	
0961500100	Electric set.
4699101105	LED module.
4699200102	Power supply.

Fil	les	to	do	οw	'n	lo	ad	
-----	-----	----	----	----	----	----	----	--

Photometric LDT files	Photometric IES files
Manual	



















Borg 6151XX0009 23.04.2020 v.09.13 www.norlys.com

Indexes		
Index	Color	RAL
6151AL	ALUMINIUM	9006
6151GR	GRAPHITE	7016





