



## Type of luminaire

Type of luminaire	Wall/ceiling luminaire.
Photometric body	Diffused, uncovered light.
Characteristics of the luminaire	A ceiling luminaire with a modern design. For lighting private areas and other architectural concepts

## General information

Materials	Powder painted aluminum cast. Lens - milky polycarbonate, UV stabilized. Silicone gasket. EPDM cable gland.
Mounting method	Mounting of the luminaire: 2 holes $\varnothing$ 5mm, spacing 150x170mm
Terminal	Connection terminals: max 3x2.5mm <sup>2</sup> , Possibility to connect the luminaire in loops, max 3x1.5mm <sup>2</sup> . Round insulated cable with a diameter of $\varnothing$ 7 ... 10.5mm
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	2,5kg / 2,5kg
Box dimensions [cm]	30,5x30,5x11

## Technical data

LED module	Lumens DLM 90C 10W xxx 230V /A V0.1 (Datasheet)
External control	Dimmers Lumens LED AC (User manual)
Light source wattage	10W
Luminaire wattage	10W
Lamp luminous flux	1100lm
Luminaire luminous flux	363lm
Light source efficiency	110lm/W
Efficiency of the luminaire	36,3lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+**

Inrush current	150mA/500 $\mu$ s
----------------	-------------------

## Spare parts

06720002	Lens.
ZS718zx0013	Service set.

## Files to download

Photometric LDT files	Photometric IES files
Manual	BIM Revit
BIM ArchiCAD	

## Indexes

Index	Color	RAL
718AL	ALUMINIUM	9006
718GR	GRAPHITE	7016
718W	WHITE	9003