



## Type of luminaire

Type of luminaire	Wall/ceiling luminaire.
Photometric body	Diffused, uncovered light.
Characteristics of the luminaire	A ceiling luminaire with a modern design. For lighting private areas and other architectural concepts

## General information

Materials	Powder painted aluminum cast. Lens - milky polycarbonate, UV stabilized. Silicone gasket. EPDM cable gland.
Mounting method	Mounting of the luminaire: 2 holes ø5mm, spacing 150x170mm.
Terminal	Connection terminals: max 3x2,5mm <sup>2</sup> , possibility to connect luminaire in loop max 3x1,5mm <sup>2</sup> . Round insulated cable with a diameter ø7...10,5mm.
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	2,43kg / 2,77kg
Box dimensions [cm]	30,5x30,5x11

## Technical data

Light source wattage	12,9W
Luminaire wattage	12,9W
Lamp luminous flux	1500lm
Luminaire luminous flux	739lm
Light source efficiency	116,3lm/W
Efficiency of the luminaire	57,3lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+**

## Spare parts

06720002	Lens.
ZS719zx0011	Service set.

## Files to download

Photometric LDT files	Photometric IES files
3D models and drawings	Manual
BIM Revit	BIM ArchiCAD

## Indexes

Index	Color	RAL
719AL	ALUMINIUM	9006
719GR	GRAPHITE	7016
719W	WHITE	9003