





Koster 724XX0010 23.07.2021 v.10.3 www.norlys.com



|--|





Type of luminaire	
Type of lumianire	Wall luminaire.
Photometric body	Single-sided, symmetric light facing down.
Characteristics of the luminaire	Modern design wall-mounted luminaire. Possibility to install on corners of architectural objects.

	architectural objects.			
General information				
Materials	Powder painted aluminum cast. Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket. EPDM cable gland.			
Mounting method	Fixing of the luminaire: 3 holes ø7mm, spacing according to the attached mounting box.			
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in loop max 3x1,5mm². A round wire in the isolation with a diameter of ø710,5mm.			
Type of light source	E27 lamp			
Net / gross weight of luminaire	2,74kg / 3,61kg			
Box dimensions [cm]	43,5x29x24			

Technical data			
E27 lamp	QA55 / LED A5560		
Light source wattage	MAX 77W / LED 9W		
ULOR	0%		
Ta Rated temperature	+25°C		

าเร	product	contains	lignt	source	or en	ergy e	etticiency	class	Λ'	, ,	

158XX0009	Mounting corner.

Accessories sold separately , xx - color of the luminaire

## Recommended light sources

Osram ECO PRO Classic 77<=>100W E27 Philips ECO Classic 70<=>100W E27

## Spare parts

06710000 Lens

## Files to download

Photometric LDT files Photometric IES files

Manual BIM Revit

BIM ArchiCAD

Indexes		
Index	Color	RAL
724AL	ALUMINIUM	9006
724GR	GRAPHITE	7016





