



Sandvik 795XX0010 23.07.2021 v.10.2 www.norlys.com



Type of luminaire	
Type of lumianire	Ceiling luminaire.
Photometric body	Single-sided, symmetric light facing down.
Characteristics of the luminaire	Classic design ceiling luminaire. For lighting private areas and public spaces.

General information		
Materials	Powder painted aluminum cast. Lens - safety glass, satin. Silicone gasket. EPDM cable gland.	
Mounting method	Fixing of the luminaire: 2 holes ø4,5mm, spacing 68x68mm.	
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in loop max 3x1,5mm². A round wire in the isolation with a diameter of ø710,5mm.	
Type of light source	LED Gu10 lamp	
Net weight of luminaire	0,59kg	
Box dimensions [cm]	12x8,5x13,5	

140		
	□80	

Technical data	
LED GU10 lamp	LED PAR16
Light source wattage	max 4W
Lamp luminous flux	~ 250lm
Light source efficiency	62,5lm/W

This product contains light source of energy efficiency class A+

Possibility to order luminaire with LED GU10 lamp Philips Master LED spot MV 250lm / 4W / 2700K / 25D (dimmable).

Accessories sold separately	
06790005	Lens.
46102501	LED GU10 lamp.

Recommended light sources

Files to download

Osram LED Parathom Advanced / Pro max 4W PAR16 Gu10 Philips Master LED max 4W PAR16 Gu10

105°				105°
90°				90°
- 75°			X	75°
60°		400		60°
45°		800		45°
700	150	1200		700

3D models and drawings		Manual	Manual	
Indexes				
Index	Color	RAL		
795AL	ALUMINIUM	9006		
795B	BLACK	9005		
795GR	GRAPHITE	7016		
795W	WHITE	9003		







