



Type of luminaire

Type of luminaire	Ceiling luminaire.
Photometric body	Single-sided, symmetric light facing down.
Characteristics of the luminaire	Classic design ceiling luminaire. For lighting private areas and public spaces.

General information

Materials	Powder painted aluminum cast. Lens - safety glass, satin. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: 2 holes $\varnothing 4,5\text{mm}$, spacing 68x68mm.
Terminal	Connection terminals: max 3x2,5mm ² , possibility to connect luminaire in loop max 3x1,5mm ² . A round wire in the isolation with a diameter of $\varnothing 7...10,5\text{mm}$.
Type of light source	LED Gu10 lamp, 25D
Light control	Phase-dimming (TRIAC).
Net weight of luminaire	0,65kg
Box dimensions [cm]	12x8,5x13,5

Technical data

LED GU10 lamp	Master LED ExpertColor 25D 3,9W \leftrightarrow 35W PAR16 Gu10
Light source wattage	3,9W
Luminaire wattage	3,9W
Lamp luminous flux	$\sim 265\text{lm}$
Luminaire luminous flux	210lm
Light source efficiency	67,9lm/W
Efficiency of the luminaire	53,8lm/W
Color temperature	2700K
Colour rendering index CRI	90
Rated life time L70/B50 at 25°C	40 000h
Power Factor luminaire	PF >0,8
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+**

Recommended light sources

Osram LED Parathom Advanced / Pro max 4W PAR16 Gu10 Philips Master LED max 4W PAR16 Gu10

Spare parts

06790005	Lens.
46102507	LED Gu10 lamp.

Files to download

Photometric LDT files	Photometric IES files
3D models and drawings	Manual

Indexes

Index	Color	RAL
796AL	ALUMINIUM	9006
796B	BLACK	9005
796GR	GRAPHITE	7016
796W	WHITE	9003