




**BASALT 3412 GR**



### BASALT

aluminium, PC / aluminium, PC / алюминий, PC


3412 ● GR 4966 ○ SI

1×E14, max 60W

IP 44



**ASSAM 4453 GR**



### ASSAM

aluminium, szkło / aluminium, glass / алюминий, стекло


4453 ● GR

1×E27, max 18W

IP 65



**INA 4907 GR**




### INA

aluminium, szkło / aluminium, glass / алюминий, стекло


4907 ● GR

1×E27, max 18W

IP 65




**STEP LED 6907 GR**




### STEP LED

aluminium / aluminium / алюминий

6907 ● GR 6908 ○ WH



**OIA LED 9103 WH**



### OIA LED

aluminium / aluminium / алюминий

9102 ● BL 9103 ○ WH



**OIA LED 9102 BL**

Item No.	POWER	COLOUR TEMP.	LUMINOUS FLUX	BEAM ANGLE	COLOUR RENDERING INDEX (CRI >=)	INPUT	SAFETY TYPE	POWER FACTOR	INGRESS PROTECTION	LIFETIME
6908, 6907	1×3W LED	3000K	310 lm	92°	80	~220-240V, 50Hz	⊕	0,57	IP 44	10 000 h
9102, 9103	1W LED	3000K	45 lm	49°	80	~220-240V, 50Hz	⊕	0,55	IP 20	10 000 h