




MYKONOS LED 10542




MYKONOS LED 10W

plastic

- 10537 3000K 10538 4000K



cut out 125 mm




MYKONOS LED 18W

plastic

- 10542 3000K 10543 4000K



cut out 175 mm




MYKONOS LED 6W

plastic

- 10535 3000K 10536 4000K



cut out 100 mm




MYKONOS LED 15W

plastic

- 10540 3000K 10541 4000K



cut out 150 mm




MYKONOS LED 24W

plastic

- 10544 3000K 10545 4000K



cut out 200 mm



EGINA LED 5W


plastic

- 10546 3000K 10547 4000K

- 10548 3000K 10550 4000K



cut out 75 mm



EGINA LED 10W

plastic

- 10551 3000K 10552 4000K


- 10553 3000K 10554 4000K



cut out 100 mm



EGINA LED 10553



EGINA LED 15W

plastic

- 10555 3000K 10556 4000K

- 10557 3000K 10558 4000K



cut out 125 mm

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10535	6W LED	3000K	360 lm	110°	>80	~220-230 V, 50/60 Hz	☐	>0.5	IP20	30000h
10536	6W LED	4000K	390 lm	110°	>80	~220-230 V, 50/60 Hz	☐	>0.5	IP20	30000h
10537	10W LED	3000K	900 lm	110°	>80	~220-230 V, 50/60 Hz	☐	>0.5	IP20	30000h
10538	10W LED	4000K	950 lm	110°	>80	~220-230 V, 50/60 Hz	☐	>0.5	IP20	30000h
10540	15W LED	3000K	1450 lm	110°	>80	~220-230 V, 50/60 Hz	☐	>0.5	IP20	30000h
10541	15W LED	4000K	1500 lm	110°	>80	~220-230 V, 50/60 Hz	☐	>0.5	IP20	30000h
10542	18W LED	3000K	1700 lm	110°	>80	~220-230 V, 50/60 Hz	☐	>0.5	IP20	30000h
10543	18W LED	4000K	1800 lm	110°	>80	~220-230 V, 50/60 Hz	☐	>0.5	IP20	30000h
10544	24W LED	3000K	2400 lm	110°	>80	~220-230 V, 50/60 Hz	☐	>0.5	IP20	30000h
10545	24W LED	4000K	2500 lm	110°	>80	~220-230 V, 50/60 Hz	☐	>0.5	IP20	30000h

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
10546	5W LED	3000K	350 lm	30°	>80	~220-230 V, 50/60 Hz	☐	>0.5	IP20	30000h
10547	5W LED	4000K	370 lm	30°	>80	~220-230 V, 50/60 Hz	☐	>0.5	IP20	30000h
10548	5W LED	3000K	330 lm	30°	>80	~220-230 V, 50/60 Hz	☐	>0.5	IP20	30000h
10550	5W LED	4000K	350 lm	30°	>80	~220-230 V, 50/60 Hz	☐	>0.5	IP20	30000h
10551	10W LED	3000K	700 lm	30°	>80	~220-230 V, 50/60 Hz	☐	>0.5	IP20	30000h
10552	10W LED	4000K	750 lm	30°	>80	~220-230 V, 50/60 Hz	☐	>0.5	IP20	30000h
10553	10W LED	3000K	650 lm	30°	>80	~220-230 V, 50/60 Hz	☐	>0.5	IP20	30000h
10554	10W LED	4000K	700 lm	30°	>80	~220-230 V, 50/60 Hz	☐	>0.5	IP20	30000h
10555	15W LED	3000K	1100 lm	30°	>80	~220-230 V, 50/60 Hz	☐	>0.5	IP20	30000h
10556	15W LED	4000K	1200 lm	30°	>80	~220-230 V, 50/60 Hz	☐	>0.5	IP20	30000h
10557	15W LED	3000K	1000 lm	30°	>80	~220-230 V, 50/60 Hz	☐	>0.5	IP20	30000h
10558	15W LED	4000K	1100 lm	30°	>80	~220-230 V, 50/60 Hz	☐	>0.5	IP20	30000h