
LUMINAIRE PHOTOMETRIC TEST REPORT

8771 CL KEA LED 30W, 3000K



Description Lines

Manufacturer:	NOWODVORSKI LIGHTING
Model name:	8771 CL KEA LED 30W,3000K
File name:	8771 CL KEA LED 30W,3000K.ltd
Date:	2019-11-06
Report number:	EF 16/11/2019/10
Diameter:	165mm
Height:	86mm
IP rating:	IP 44/IP 20
Protection class:	II
Dimmable:	No

Equipment

Test system:	EVERFINE GO-2000B_V1 SYSTEM V2.00.417
Temperature:	25 +/-1 °C
Humidity:	65.0%
γ interval:	2 deg
C interval:	10 deg
γ range:	0-180 deg
Measurement distance:	6.56 m

Nowodvorski sp. j.

ul. Bojemskiego 11, 42-202 Częstochowa, POLSKA, NIP: PL 5731015208


Tel. +48 34 344 91 10, 344 91 11, fax +48 34 344 91 12

www.nowodvorski.com

Photometric data

Total luminous flux:	1886.93 lm
Color temperature:	3018 K
x:	0.4354
y:	0.4032
Color rendering index:	95.9
Wattage:	27.091 W
U	220.65 V
I	0.1272 A
Power factor:	0.9652
Luminous efficacy:	69.65 lm/W
Flux in lower hemisphere:	98.7%
Flux in upper hemisphere:	1.3%
Maximum luminous intensity:	1565 cd
Light output ratio (LOR):	100.00%

Beam cone diagram Beam angle 65°




Nowodvorski sp. j.

ul. Bojemskiego 11, 42-202 Częstochowa, POLSKA, NIP: PL 5731015208

Tel. +48 34 344 91 10, 344 91 11, fax +48 34 344 91 12


www.nowodvorski.com

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Luminous intensity [cd]
 C0-C180 ————
 C90-C270 ————

Spectral distribution



Nowodvorski sp. j.
 ul. Bojemskiego 11, 42-202 Częstochowa, POLSKA, NIP: PL 5731015208
 Tel. +48 34 344 91 10, 344 91 11, fax +48 34 344 91 12
www.nowodvorski.com