



STRAIGHT CEILING LED L 7551



STRAIGHT CEILING LED M 7558



STRAIGHT CEILING LED S 7597




STRAIGHT CEILING LED L

painted steel, plastic PMMA

7551 7556 7600

1xLED TUBE T8, max 22W, included



STRAIGHT CEILING LED M

painted steel, plastic PMMA

7553 7558 7598

1xLED TUBE T8, max 16W, included



STRAIGHT CEILING LED S

painted steel, plastic PMMA

7552 7557 7597

1xLED TUBE T8, max 11W, included

Name	Size	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Power factor	Lifetime	Material
LED TUBE T8	60 cm	11W LED	3000K	1700 lm	120°	≥80	220-230 V, 50/60 Hz	>0,5	30000h	CLEAR GLASS
LED TUBE T8	90 cm	16W LED	3000K	2300 lm	120°	≥80	220-230 V, 50/60 Hz	>0,5	30000h	CLEAR GLASS
LED TUBE T8	120 cm	22W LED	3000K	3200 lm	120°	≥80	220-230 V, 50/60 Hz	>0,5	30000h	CLEAR GLASS

GRAPHITE P010 RAL 7016 WHITE P004 RAL 9003 BLACK P013 RAL 9005

