

# **Product Datasheet**

www.1-light.eu

### 06 Downlights Fixed LED>The Dark Light Project Range

## 10110TD/W/C



10W LED recessed downlight, IP54. Suitable for Indoor/Outdoor installation.

Complete with 250mA driver.

Complies with standard EN60598-1 and any other specific standards.













#### Downloads









#### Dimensions



#### **Physical Specification**

06 Downlights Fixed LED
The Dark Light Project Range
10110TD/W/C
White
Aluminium
Circular
67mm
115mm
95mm
Yes
110mm
Yes

Outdoor	Yes	Pobrano z mamadecor.pl
Adjustable	No	
lectrical Characteristics		
iectrical Characteristics		
Gear	External-Included	
Fitting + Driver		
Input Voltage	220-240V	
50 Hz	Yes	
60 Hz	Yes	
Safety Class		
Power(Watts)	10W	
IP Rating	IP54	
Light Source	LED built in	
Dimmable	No	
F Mark	F	
Fitting		
Input Type	Constant Current	
Input Current	250mA	
Voltage	39V	
Safety Class	<u> </u>	
Power(Watts)	9W	
IP Rating	IP54	
Light Source	LED built in	
LED Type	SMD 2835	
LED Brand	Epistar	
F Mark	F	
Gear		
Gear Type	Led Driver	

Input Voltage	220-240V Pobra	no z mamadecor.pl
50 Hz	Yes	
60 Hz	Yes	
Power(Watts)	7-9,2W	
Power Factor	0,9	
Constant Current	Yes	
Output	250mA	
Voltage Range	30-40V	
IP Rating	IP20	
Safety Class		
Dimmable	No	
Housing Material	Plastic	
Output Terminal	Cable	
Brand	ONE	
Illumination Data		
Colour Temperature	4000K	
Lumen Output	950lm	
Light Efficiency	95lm/W	
CRI	80	
Beam Angle	60°	
Illumination Diagram		
Dark Light	Yes	
Packing Info		
Box Length	14cm	
Box Width	14cm	
Box Height	8cm	
Pcs/Carton	30	
Pcs/Carton  Barcode		

Certification & Warranty	
Warranty	2 Years
Weee Directive	Yes

# switch to one light!

