

02 Recessed Spots Fixed LED>The Trimless Mini Range Aluminium

10112BTR/BS/W



12W COB LED 2-Step trimless Recessed spot, IP20, for general application. Requires 700mA constant current driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Must be ordered separately



89015A



89015AT

Physical Specification

| | |
|---------------------------|-----------------------------------|
| Item Group | 02 Recessed Spots Fixed LED |
| Family | The Trimless Mini Range Aluminium |
| Order Code | 10112BTR/BS/W |
| Colour | Brass Reflector |
| Material | Aluminium |
| Shape | Circular |
| Height | 92mm |
| Diameter | 64mm |
| Cutout Hole Diameter | 70mm |
| Recessed trimless ceiling | Yes |
| Depth Required | 110mm |
| Indoor | Yes |
| Adjustable | No |

Electrical Characteristics

Fitting

| | |
|---------------|------------------|
| Input Type | Constant Current |
| Input Current | 700mA |
| Safety Class | III |
| Power(Watts) | 12W |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | COB |

LED Brand

Bridgelux

Pobrano z mamadecor.pl

Cable Length

40cm

F Mark



Illumination Data

Colour Temperature

3000K

Lumen Output

1100lm

Light Efficiency

91,67lm/W

CRI

90

Beam Angle

40°

Illumination Diagram



Dark Light

Yes

Packing Info

Pcs/Carton

48

Barcode

5291889070078

HS Code

9405409900

Certification & Warranty

Warranty

5 Years

Weee Directive

Yes

switch to
one light!

one
LIGHT

