

02 Recessed Spots Fixed LED>The 12W COB IP65 Range

10112P/AL/W



12W COB LED recessed spot, IP64, for general application.

Suitable for bathroom installation.

Requires 700mA constant current driver.


Complies with standard EN60598-1 and any other specific standards.




Downloads



Dimensions



Gallery



Must be ordered separately



89015A



89015AT


Physical Specification

Item Group	02 Recessed Spots Fixed LED
Family	The 12W COB IP65 Range
Order Code	10112P/AL/W
Colour	Aluminium
Material	Natural Aluminium
Shape	Circular
Height	85mm
Diameter	83mm
Cutout Hole Diameter	70mm
Recessed Ceiling	Yes
Depth Required	105mm
Indoor	Yes
Outdoor	Yes
Adjustable	No


Electrical Characteristics

Fitting

Input Type	Constant Current
Input Current	700mA
Safety Class	III
Power(Watts)	12W
IP Rating	IP64
Light Source	LED built in

LED Type	COB
LED Brand	Bridgelux
Cable Length	40cm
F Mark	

Illumination Data

Colour Temperature	3000K
Lumen Output	1100lm
Light Efficiency	91,67lm/W
CRI	80
Beam Angle	40°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Length	9cm
Box Width	9cm
Box Height	10cm
Box Weight	0,326kg
Pcs/Carton	50
Barcode	5291889038955
HS Code	9405409900

Certification & Warranty

Warranty

3 Years

Pobrano z mamadecor.pl

Weee Directive

Yes

switch to
one light!

one
LIGHT

